

PNEUMATICALLY ACTUATED VALVES

CONTACT INFORMATION

COMPANY _____ TELEPHONE _____

CONTACT _____ FAX _____

DATE _____ E-MAIL _____

VALVE AND MEDIA INFORMATION

VALVE TYPE/SIZE _____ TEMPERATURE _____

MEDIA _____ LINE PRESSURE _____

TORQUE REQUIRED (IF CUSTOMER OWNED VALVE) _____

BODY & TRIM MATERIAL: BALL VALVE

BODY MATERIAL	END CONNECTIONS	SEAT MATERIAL
<input type="checkbox"/> CARBON STEEL X SS	<input type="checkbox"/> NPT	<input type="checkbox"/> TFE
<input type="checkbox"/> BRONZE	<input type="checkbox"/> SOCKET WELD	<input type="checkbox"/> RTFE
<input type="checkbox"/> BRASS X SS	<input type="checkbox"/> BUTT WELD	<input type="checkbox"/> DELRIN
<input type="checkbox"/> BRASS	<input type="checkbox"/> CLAMP END	<input type="checkbox"/> PEEK
<input type="checkbox"/> STAINLESS STEEL	<input type="checkbox"/> 150# FLANGED	<input type="checkbox"/> NOVA
<input type="checkbox"/> PVC	<input type="checkbox"/> 300# FLANGED	<input type="checkbox"/> METAL
<input type="checkbox"/> CPVC		

BODY & TRIM MATERIAL: BUTTERFLY VALVE

BODY MATERIAL	DISC MATERIAL	SEAT MATERIAL
<input type="checkbox"/> CAST IRON	<input type="checkbox"/> DUCTILE IRON	<input type="checkbox"/> EPDM
<input type="checkbox"/> STAINLESS STEEL	<input type="checkbox"/> STAINLESS STEEL	<input type="checkbox"/> VITON
<input type="checkbox"/> PVC	<input type="checkbox"/> ALUMINUM BRONZE	<input type="checkbox"/> BUNA-N
<input type="checkbox"/> CPVC	<input type="checkbox"/> CPVC	<input type="checkbox"/> TFE
<input type="checkbox"/> POLYPROPYLENE	<input type="checkbox"/> POLYPROPYLENE	<input type="checkbox"/> METAL
END CONNECTIONS		
<input type="checkbox"/> WAFER	<input type="checkbox"/> LUG	

ACTUATOR INFORMATION

ACTUATOR TYPE DOUBLE ACTING SPRING RETURN

AVAILABLE AIR SUPPLY

80 PSI 60 PSI 40 PSI

70 PSI 50 PSI OTHER

FAIL POSITION (SPRING RETURN ONLY)

FAIL OPEN (CCW) FAIL CLOSED (CW-STANDARD)

DECLUTCHABLE MANUAL OVERRIDE Yes No

APPLICATION AND ENVIRONMENT

OPTIONAL ACCESSORIES

SOLENOID VALVE

VOLTAGE OPTIONS	NEMA RATING	CONNECTION
<input type="checkbox"/> 115 VAC <input type="checkbox"/> 230 VAC	<input type="checkbox"/> 4/4X	<input type="checkbox"/> DIN STRAIN RELIEF
<input type="checkbox"/> 24 VAC <input type="checkbox"/> 24 VDC	<input type="checkbox"/> 7/9	<input type="checkbox"/> DIN 1/2" CONDUIT
		<input type="checkbox"/> FLYING LEADS

LIMIT SWITCH

VISUAL	NEMA RATING	SWITCH TYPE
<input type="checkbox"/> DOME INDICATOR	<input type="checkbox"/> 4/4X	<input type="checkbox"/> 2 SPDT (MECHANICAL)
<input type="checkbox"/> FLAT TOP	<input type="checkbox"/> 7/9	<input type="checkbox"/> 2 SPST (PROXIMITY)

POSITIONER (MODULATING SERVICE)

TYPE	NEMA RATING	OPTIONS
<input type="checkbox"/> 3-15 PSI PNEUMATIC	<input type="checkbox"/> 4/4X	<input type="checkbox"/> 2 SPDT SWITCHES
<input type="checkbox"/> 4-20MA ELECTRO-PNEUMATIC	<input type="checkbox"/> 7/9	<input type="checkbox"/> 2 SPST SWITCHES
VISUAL	<input type="checkbox"/> INTRINSICALLY SAFE	<input type="checkbox"/> 4-20MA TRANSMITTER
<input type="checkbox"/> DOME INDICATOR		<input type="checkbox"/> 0-1K FEEDBACK
<input type="checkbox"/> FLAT TOP		<input type="checkbox"/> GAUGES